

LED Premium Street Light 60w c/w Photocell NEMA Dusk til Dawn Sensor Flicker Free

£161.69


8,400lm



60W
Replaces
100W SON



LED Premium Street Light DIMENSIONS




Performance-Optimized Design & Robust Construction





PHOTOCELL ENABLED

FOR UP TO 80% SAVINGS ON ELECTRICITY



DURABLE, ROBUST AND DEPENDABLE

ULTRAVIOLET PROTECTION



DARK SKY FRIENDLY



PRODUCT INFORMATION

| | |
|------------------|----------------------------|
| LED Type | SMD3030 LEDs |
| Warranty | 5 Year |
| Part L Compliant | Yes |
| Dimensions | 617mm x 212mm x 118mm |
| Weight | 5.35kg |
| Windage | 0.13m ² |
| Socket Type | Optional 3 pin NEMA Socket |
| Equivalent to | 70 MHL |

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|---------------|
| Power Consumption | 60W |
| Input Voltage | 100-280V AC |
| Power Factor | >0.96 |
| Operating Temperature | -20°C to 65°C |
| L70 Rated Lifetime | +100,000hrs |

PRODUCT INFORMATION

TECHNICAL SPECIFICATIONS

Ingress Protection IP66

LUMEN PERFORMANCE

Luminous Efficiency 140lm/W

Beam Angle 80° x 150°

CRI (Colour Rendering Index) >80Ra

Lumen Output 8,400lm

AVAILABLE OPTIONS

Colour Temperature 3000K (Dark Sky Friendly- 0% ULOR) 4000K

3-Hour Emergency Version No

Built-in Microwave Occupancy Detector No

1-10V Dimmable Available on Request

DALI Dimmable Available on Request

****Fitting Comes inclusive with integral 3-Pin NEMA Socket and Lucy Zodion 70lux Photocell****

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 20W - 240W (2,800-33,000lm). IP66 design for exterior environments, with a low profile, sleek silver anodised aluminum body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)



Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text_phone 03333 444 943
sales@theledstore.co | <https://theledstore.co/>